

# **DOUBLE SIDED FOAM TAPE**

## **Product Type:**

**Double Sided Foam Tape** 

#### Specification:

- Material: Foamed IXPE
- Polyethylene foam tape
- Acrylic adhesive
- UV resistant, water resistance, and weather resistance



## Application:

Various sizes of double sided foam tape, coated with an aggressive solvent acrylic adhesive, ideal for the fitting of trims and number plates and for many other uses, also suited to hostile outdoor environments.

#### Storage:

Clean and dry in a well ventilated area, Stored under these conditions shelf life will be 12 months.

**Technical Spec:** 

reclinical Spec.			
Description	Value		
Foam Thickness (mm)	$0.80 \pm 0.10$		
Total Thickness (mm)	0.95±0.15		
Tack (#)	≥12		
Holding strength (Min 70 °C 500g/25mm x 25mm)	≥500		
180° Peel Adhesive (N/25mm)	≥16		
Tensile strength (N/10mm)	≥8		
Elogation (%)	≥250		
Heat Resistance (°C)	-4 to 90		

### **Product Code:**

Code	Description	Size	Colour
ADSFT6X10	Double Sided Foam Tape	6mm x 10m	Black
ADSFT9X10	Double Sided Foam Tape	9mm x 10m	Black
ADSFT12X10	Double Sided Foam Tape	12mm x 10m	Black
ADSFT19X10	Double Sided Foam Tape	19mm x 10m	Black
ADSFT25X10	Double Sided Foam Tape	25mm x 10m	Black
ADSFT38X10	Double Sided Foam Tape	38mm x 10m	Black
ADSFT50X10	Double Sided Foam Tape	50mm x 10m	Black

Datasheet Ref: FOAMTAPE Issue: 1 Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.