

## Individually Switched Surge Protected Extension Lead with USB

### Specifications:

- Mains extension with two USB charging ports.
- Individually switched sockets with neon power indicators
- Rated at 13A
- USB ports rated at 5V, 2.4A
- Conforms to BS1363/A, BS5733/A
- UK mains plug (type G), as used in the UK, IRL, Cyprus, Saudi Arabia, Malta and many others.

### Approvals:



### Complies to:



Code Table:

Code	Description	No.of Outlets	Colour
SH15642	4 Gang Surge Protected Extension Lead 2m White with 4 x Neon Switch and 2xUSB	4 Gang	White
SH15643	5 Gang Surge Protected Extension Lead 2m White with 5 x Neon Switch and 2xUSB	5 Gang	White
SH15644	6 Gang Surge Protected Extension Lead 2m White with 6 x Neon Switch and 2xUSB	6 Gang	White
SH15645	4 Gang Surge Protected Extension Lead 2m Black with 4 x Neon Switch and 2xUSB	4 Gang	Black
SH15646	5 Gang Surge Protected Extension Lead 2m Black with 5 x Neon Switch and 2xUSB	5 Gang	Black
SH15647	6 Gang Surge Protected Extension Lead 2m Black with 6 x Neon Switch and 2xUSB	6 Gang	Black

*Dimensions and images may differ from those shown*

Datasheet Ref: EXINDVISURUSB

Issue: 1

Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.

**C & C Cables Limited** Unit OA, Time Technology Park, Blackburn Road, Simonstone, Burnley, Lancs, BB12 7NQ, UK