

Suppliers of Quality Assured Cables

# MICROPHONE CABLE MIC0018BLK

## **Product Description:**

MICROPHONE CABLE DOUBLE SHIELDED 100M

## **Application:**

Blanced microphone cable suitable for use in studios, P.A equipment, and general audio applications

## **Construction:**

Conductor:	10/0.12mm (BC OFC)
Insulation:	PE
Insulation Color:	RED,WHITE
Insulation Dia./Thickness:	1.0±0.10mm / 0.20mm
Wrap:	AL
Shielding:	30±2/0.12mm (BC OFC)
Shielding Coverage:	47%
Jacket:	PVC
Jacket Color:	Black
Jacket Dia./Thickness:	4.0±0.1*8.0±0.2 mmmm / 0.8mm

### **Electrical Characteristics:**

Rated Temperature:  $60^{\circ}$ C Conductor Resistance (Max.at  $20^{\circ}$ C):  $168.07\Omega$ /km

Packaging: 100M/Plastic Spool

Other Standard: RoHS Compliant

Datasheet Ref: Microphone Cable

Issue: 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.

C & C Cables Limited Unit OA, Time Technology Park, Blackburn Road, Simonstone, Burnley, Lancs, BB12 7NQ, UK

