

MICROPHONE CABLE MIC0019BLU

Product Description:

CABLE BALANCED MULTICORE 4 PAIR 50M



Balanced multi-core cable ideal for use in studio, stage and general A/V applications



Construction:

0	00/0.40 (DO 050)
Conductor:	20/0.10 mm (BC OFC)
Insulation:	PE
Insulation Color:	Red, White
Insulation Dia./Thickness:	1.1±0.10 mm / 0.29±0.08 mm
Drain Wire	7/0.20TC
Wrap:	AL-Foil
Covering	PVC
Covering Color	Blue
Covering Dia./Thickness:	3.0±0.10 mm / 0.36±0.10 mm
Jacket:	PVC
Jacket Color:	Blue
Jacket Dia./Thickness:	10.0±0.3 mm / 1.38±0.15 mm

Electrical Characteristics:

Rated Temperature: 60°C

Conductor Resistance (Max.at 20°C): 121.01Ω/km

Packaging:

50M/Wooden Spool

Other Standard:

RoHS Compliant

Datasheet Ref: Microphone Cable

Issue: 1

Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.