

MICROPHONE CABLE

MIC0025BLK

Product Description:

CABLE MICROPHONE UNBALANCED BLACK 100M



Professional, unbalanced microphone cable suitable for use in audio applications



Construction:

Conductor:	20/0.12mm (BC OFC)
Insulation:	PE
Insulation Color:	Red
Insulation Dia./Thickness:	1.40±0.10mm / 0.42mm±0.10mm
Filler:	
Shielding:	30±2/0.12mm (BC OFC)
Shielding Coverage:	57%
Jacket:	PVC
Jacket Color:	Black
Jacket Dia./Thickness:	5.0±0.20mm / 1.63±0.10mm

Electrical Characteristics:

Rated Temperature: 60°C

Conductor Resistance (Max.at 20°C): 88.24Ω/km

Packaging:

100M/Plastic Spool

Other Standard:

RoHS Compliant

Datasheet Ref: Microphone Cable

Issue: 1

Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.

C & C Cables Limited Unit OA, Time Technology Park, Blackburn Road, Simonstone, Burnley, Lancs, BB12 7NQ, UK