



Solar Cable – TUV Approved

Product Type:
Solar Cable

Application:

This cable is suitable for inter-connections within photovoltaic systems such as solar panel arrays. They are manufactured in accordance with various British and International Standards and are designed to withstand severe environmental conditions.

Standards:

EN50618:2014
REACH and RoHS compliant

DESCRIPTION	H1Z2Z2-K 1x6mm ² Solar Cable	
P/N	6012241ABLK, 6012241ABLK50M, 6012244ARED, 6012244ARED50M	
CONDUCTOR	Material:	Tinned plated copper
	Construction:	84/0.285±0.015
	Dia.:	3.0mm
INSULATION	Material:	XLPO
	Overall Diameter:	4.5±0.1mm
	Average Thickness:	≥0.7mm
	Min. Thickness	≥0.53mm
	Colour:	Black, Red/Black
JACKET	Material:	XLPO
	Overall Diameter:	6.3±0.2mm
	Average Thickness:	≥0.8mm
	Min. Thickness	≥0.58mm
	Colour:	Black, Red
ELECTRIC PROPERTIES	Rated Voltage:	AC1.0/1.0KV, DC1.5KV
	Rated Temperature:	-40°C - 90°C
	Conductor Resistance @20°C	≤3.39Ω/km
	Insulation Resistance @20°C	≥500MΩ.km
	Voltage Withstand Test:	AC: 6.5KV, DC: 15KV, 5min
	Spark Electro Mechanical Voltage:	7KV
	Short-Circuit Temperature:	≤200°C/5s
INSULATION	Min Tensile Strength:	≥8.0 N/mm ²
	Min. Elongation at Break	≥125%
	Flame Test:	EN60332-1-2
LIFETIME	25 years	
PACKAGING	50M/reel, 100M/reel	

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.