



Solar Extension Lead

Product Type:
Solar Extension Lead

Standards:
IEC62852:2014, EN50618:2014
REACH and RoHS compliant

Description	Solar Extension Cable
P/N	SC4MM, SC6MM
Suitable Wire Specifications	4mm ² , 6mm ²
Rated voltage	DC 1500V
Rated current	30A
Connector type	60122CON05
Photovoltaic cable type	H1Z2Z2-K
Cable colour	Black, Red
Locking system	Locking type
Degree of protection	IP65/IP68
Ambient temperature range	-40°C~+85°C
Upper temperature limit	100°C
Connector contact resistance	≤0.5mΩ
Withstand voltage test	6.5KV, 1min
Flame class	UL94-V0
Compatibility	Compatible with MC4 connectors
Salt spray test	Degree of severity 6
Damp heat test	No damage occurred which could impair normal use
Insert & withdraw force	Insertion force ≤50N, withdraw force ≥50N
Connector pulling force	≥200N
Length	1M, 2M, 3M, 5M
Lifetime	25 years

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.