

UTP CCA Conductors Grey 305m Reel

Product Type:

Lan Cable

Specification:

- Economy network cable
- CCA (Copper Clad Aluminium) conductors
- Impedance 100±15Ω
- CPR Cat Eca
- Not recommended for POE use
- Cable Shielding:Unscreened
- LAN Category: CCA (No POE Use)
- Wire Gauge:25AWG
- Conductor Area CSA:0.2mm²
- Reel Length (Imperial):1000ft
- Reel Length (Metric):305m
- No. of Pairs:4 Pair
- Jacket Colour:Grey
- No. of Max Strands x Strand Size:Solid
- Jacket Material:Polyester, PVC
- Conductor Material: Copper Coated Aluminium
- External Diameter:5.2mm



Other Electric Data:

Frequency	Impedance	RL	ATT	NEXT	ELFEXT	PSNEXT	PSELFEXT	SKW	NVP
Mhz	ohm	≥dB/100M	≤dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≤ns/100M	
1		20.0	2.04	65.3	63.8	62.3	60.8		
4		23.0	4.1	56.3	51.7	53.3	48.7		
10		25.0	6.5	50.3	43.8	47.3	40.8]	
16	100±15	25.0	8.2	47.3	39.7	44.3	36.7	≤45	66%
20		25.0	9.3	44.5	37.7	42.8	34.7		
31.25		23.6	11.6	42.9	33.9	39.9	30.9]	
62.5		21.5	17.0	38.4	27.8	35.4	24.8]	
100		20.1	22.0	35.3	23.8	32.3	20.8]	

These Electric data are subject to Max. 80 meters cable

Datasheet Ref: U-UTP C5 PVC Issue: 1 Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.

C & C Cables Limited Unit OA, Time Technology Park, Blackburn Road, Simonstone, Burnley, Lancs, BB12 7NQ, UK